

















Profilübersicht und statische Profilwerte Serie Lambda duo 90 Fenster Profile overview and static profile values for Series Lambda duo 90 window

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page
		L(cm) < 200	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology								L(cm) < 200	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology					
			ab from ≥200	ab from >250	ab from > 300	ab from > 400						ab from ≥200	ab from >250	ab from > 300	ab from > 400		
	B 840000	30	38	43	47	51	333	7		B 840007	27	34	38	41	44	268	16
	B 840001	33	42	48	53	58	353	7		B 840008	29	37	42	46	50	288	16
	B 840002	35	45	53	58	65	373	8		B 840009	32	42	48	53	58	308	16
	B 840003	37	49	57	64	72	395	8		B 840020	34	44	51	56	62	412	12
	B 840004	41	54	65	73	84	435	9		B 840021	36	47	55	61	68	431	13
	B 840005	44	60	73	83	96	453	10		B 840022	38	50	59	66	75	451	13
	B 840006	36	46	54	59	66	418	11		B 840027	-	-	-	-	-	340	14

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia